



WIRE RANGE A.W.G. mm ²	ITEM NO.	Dimensions (mm)						
		Ød2	B	L	E	F	Ød	ØD
300/350MCM A.W.G. 185 mm ²	CT185-12	13.0	34.0	78.0	32.0	29.0	18.5	23.5
	CT185-14	15.0	34.0					
	CT185-16	17.0	34.0					
400/450MCM A.W.G. 240 mm ²	CT240-14	15.0	38.5	92.0	38.0	34.0	21.0	26.5
	CT240-16	17.0	38.5					
	CT240-18	19.0	38.5					
500MCM A.W.G. 300 mm ²	CT300-14	15.0	43.5	101.0	42.0	37.0	23.5	30.0
	CT300-16	17.0	43.5					
	CT300-18	19.0	43.5					
600/750MCM A.W.G. 400 mm ²	CT400-16	17.0	53.0	114.0	44.0	44.0	28.5	36.5
	CT400-18	19.0	53.0					
	CT400-20	21.0	53.0					
800/1000MCM A.W.G. 500 mm ²	CT500-16	17.0	56.0	124.0	48.0	48.0	30.0	39.0
	CT500-18	19.0	56.0					
	CT500-20	21.0	56.0					
1000/1250 MCM A.W.G. 625 mm ²	CT625-16	17.0	63.5	130.0	52.0	51.0	34.5	44.0
	CT625-18	19.0	63.5					
	CT625-20	21.0	63.5					