



※ 線末端子套管(軟式套管)需另外諮詢
 ※ Terminals Soft Sleeves for Extra Quote

WIRE RANGE A.W.G. mm ²	ITEM NO.	Stud Size		Dimensions (mm)							
		American	Metric	Ød2	B	F	L	E	Ød	ØD	T
22-16 A.W.G. 0.5-1.5mm ²	G-R1-3NB	#4	3.0	3.2	5.5	4.8	12.5	5.0	1.7	3.4	0.75
	G-R1-3.5SNB	#6	3.5	3.7	5.5	4.8	12.5				
	G-R1-3.5NB	#6	3.5	3.7	6.6	6.3	14.6				
	G-R1-4SNB	#8	4.0	4.3	6.6	6.3	14.6				
	G-R1-4NB	#8	4.0	4.3	8.0	7.0	16.0				
	G-R1-5NB	#10	5.0	5.3	8.0	7.0	16.0				
	G-R1-6NB	1/4	6.0	6.4	11.6	11.1	21.9				
	G-R1-8NB	5/16	8.0	8.4	11.6	11.1	21.9				
	G-R1-10NB	3/8	10.0	10.5	13.6	13.9	25.7				
	G-R1-12NB	1/2	12.0	12.0	13.0	19.0	16.0				
16-14 A.W.G. 1.5-2.5 mm ²	G-R2-3NB	#4	3.0	3.2	6.6	4.3	12.6	5.0	2.3	4.1	0.8
	G-R2-3.5SNB	#6	3.5	3.7	6.6	4.3	12.6				
	G-R2-3.5NB	#6	3.5	3.7	6.6	6.3	14.6				
	G-R2-4SNB	#8	4.0	4.3	6.6	6.3	14.6				
	G-R2-4NB	#8	4.0	4.3	8.5	7.8	17.0				
	G-R2-5SNB	#10	5.0	5.3	8.5	7.8	17.0				
	G-R2-5NB	#10	5.0	5.3	9.5	7.3	17.0				
	G-R2-6NB	1/4	6.0	6.4	12.0	11.0	22.0				
	G-R2-8NB	5/16	8.0	8.4	12.0	11.0	22.0				
	G-R2-10NB	3/8	10.0	10.5	13.6	13.9	25.7				
G-R2-12NB	1/2	12.0	12.0	13.0	19.0	16.0	30.6				
14-12 A.W.G. 2.5-4 mm ²	G-R3-4NB	#8	4.0	4.3	8.0	7.8	17.8	6.0	2.9	5.1	1.0
	G-R3-5NB	#10	5.0	5.3	8.0	7.8	17.8				
	G-R3-5LNB	#10	5.0	5.3	12.0	9.4	21.4				
	G-R3-6NB	1/4	6.0	6.4	12.0	9.4	21.4				
	G-R3-8NB	5/16	8.0	8.4	15.0	13.3	26.8				
	G-R3-10NB	3/8	10.0	10.5	15.0	13.3	26.8				
	G-R3-12NB	1/2	12.0	12.0	13.0	19.2	16.0				
12-10 A.W.G. 4-6 mm ²	G-R5-3.5NB	#6	3.5	3.7	7.2	5.9	15.5	6.0	3.4	5.6	1.0
	G-R5-4SNB	#8	4.0	4.3	7.2	5.9	15.5				
	G-R5-4NB	#8	4.0	4.3	9.5	8.3	19.0				
	G-R5-5NB	#10	5.0	5.3	9.5	8.3	19.0				
	G-R5-6NB	1/4	6.0	6.4	12.0	10.5	22.5				
	G-R5-8NB	5/16	8.0	8.4	15.0	13.7	27.2				
	G-R5-10NB	3/8	10.0	10.5	15.0	13.7	27.2				
	G-R5-12NB	1/2	12.0	12.0	13.0	19.2	16.0				

8 A.W.G. 8 mm ²	G-R8-3.5NB	#6	3.5	3.7	8.0	9.3	21.8	8.5	4.5	7.1	1.2
	G-R8-4SNB	#8	4.0	4.3	8.0	9.3	21.8				
	G-R8-4NB	#8	4.0	4.3	12.0	9.3	23.8				
	G-R8-5SNB	#10	5.0	5.3	9.0	9.3	22.3				
	G-R8-5NB	#10	5.0	5.3	12.0	9.3	23.8				
	G-R8-5LNB	#10	5.0	5.3	15.0	13.8	29.8				
	G-R8-6NB	1/4	6.0	6.4	12.0	9.3	23.8				
	G-R8-6LNB	1/4	6.0	6.4	15.0	13.8	29.8				
	G-R8-8NB	5/16	8.0	8.4	15.0	13.8	29.8				
	G-R8-10NB	3/8	10.0	10.5	15.0	13.8	29.8				
	G-R8-12NB	1/2	12.0	13.0	20.0	15.0	33.5				
6 A.W.G. 14 mm ²	G-R14-4NB	#8	4.0	4.3	12.0	13.3	29.8	10.5	5.8	9.0	1.5
	G-R14-5NB	#10	5.0	5.3	12.0	13.3	29.8				
	G-R14-6NB	1/4	6.0	6.4	12.0	13.3	29.8				
	G-R14-6LNB	1/4	6.0	6.4	16.0	14.5	33.0				
	G-R14-8NB	5/16	8.0	8.4	16.0	14.5	33.0				
	G-R14-10NB	3/8	10.0	10.5	16.0	14.5	33.0				
	G-R14-11NB	7/16	11.0	11.5	22.0	19.5	41.0				
	G-R14-12NB	1/2	12.0	13.0	22.0	19.5	41.0				
4 A.W.G. 22 mm ²	G-R22-5SNB	#10	5.0	5.3	12.0	12.0	30.0	12.0	7.7	11.5	1.8
	G-R22-5NB	#10	5.0	5.3	16.5	13.5	33.7				
	G-R22-6SNB	1/4	6.0	6.4	12.0	12.0	30.0				
	G-R22-6NB	1/4	6.0	6.4	16.5	13.5	33.7				
	G-R22-8SNB	5/16	8.0	8.4	12.0	12.0	30.0				
	G-R22-8NB	5/16	8.0	8.4	16.5	13.5	33.7				
	G-R22-10SNB	3/8	10.0	10.5	16.5	13.5	33.7				
	G-R22-10NB	3/8	10.0	10.5	17.5	16.0	36.7				
	G-R22-11NB	7/16	11.0	11.5	22.0	19.5	42.5				
	G-R22-12NB	1/2	12.0	13.0	22.0	19.5	42.5				
2 A.W.G. 38 mm ²	G-R38-5NB	#10	5.0	5.3	15.3	17.4	39.0	14.0	9.4	13.3	1.8
	G-R38-6SNB	1/4	6.0	6.4	15.3	17.4	39.0				
	G-R38-6NB	1/4	6.0	6.4	22.0	17.7	42.7				
	G-R38-8SNB	5/16	8.0	8.4	15.3	17.4	39.0				
	G-R38-8NB	5/16	8.0	8.4	22.0	17.7	42.7				
	G-R38-10SNB	3/8	10.0	10.5	15.3	17.4	39.0				
	G-R38-10NB	3/8	10.0	10.5	22.0	17.7	42.7				
	G-R38-11NB	7/16	11.0	11.5	22.0	17.7	42.7				
	G-R38-12NB	1/2	12.0	13.0	22.0	17.7	42.7				